

# PACKAGED TERMINAL AIR CONDITIONERS & HEAT PUMPS



42" PTAC SHOWN ABOVE



Auto-restart function



Compressor 3 minutes delay protection



LED indicators and control buttons



Automatic quick warm-up



Automatic evaporator freeze protection



Unit configuration - the unit can display in either °C or °F



High temperature protection in heating operation




Self-diagnostics - our PTAC's have a self-check error function, error code will be shown on electric display panel

## ACCESSORIES & REPLACEMENT PARTS:



Wired  
Thermostat



Rd Sleeve



Stamped  
Aluminum Grille



Extruded  
Architectural  
Grille



Condensate  
Drain Kit  
(Included with  
wall sleeve)

	MODEL	UNIT	MWDUP-09AEN1-MK3	MWDUP-12AEN1-MJ5	MWDUP-15AEN1-MI6
<b>COOLING</b>	Capacity (Rated)	Btu/h	9000	12000	14700
	Capacity (Min.-Max.)	Btu/h	8800-9000	11800-12000	14500-14700
	EER		11.3	10.5	9.6
	Refrigerant		R410A	R410A	R410A
<b>HEATING</b>	Capacity (Rated)	Btu/h	8100	10800	13500
	COP		3.4	3.2	3
	AUXILIARY HEATING	W	3500	3500	3500
	Indoor Airflow (Lo-Med-Hi)	CFM	394X417X435	411-423-435	394-405-423
	Indoor Noise Level (Lo-Med-Hi)	dB(A)	25-30-36.5	45-50-53	45-50-53
	Outdoor Noise Level	dB(A)	61	66	66
	Ambient Operating Temperature Range	Cooling °F Heating °F	64 ~ 109 23 ~ 76	64 ~ 109 23 ~ 76	64 ~ 109 23 ~ 76
	Condensate Drain		1/2"	1/2"	1/2"
	Dimension (WxDxH)	in	42X21X16	42X21X16	42X21X16
	Weight	lb	107	118	120
<b>ELECTRICAL</b>	V/ph/Hz		208~230V/1ph/ 60Hz	208~230V/1ph/ 60Hz	208~230V/1ph/ 60Hz
	Power Input	Cooling Heating	796W 716W	1142W 10800W	1531W 1323W