

DUCTING

FLEXMAXX DUCTING SYSTEM

- Mechanically bonded
- Acoustically rated
- Mylar vapor barrier
- UL listed
- No adhesives
- Low permeable vapor barrier
- Corrosive resistant helix
- Lightweight
- Thermal reliability
- Economical 25ft lengths



NOTE: THIS UL CLASS 1 PRODUCT HAS A FLAME SPREAD RATING OF NOT OVER 25 WITHOUT EVIDENCE OF CONTINUED PROGRESSIVE COMBUSTION AND A SMOKE DEVELOPED RATING OF NOT OVER 50.

- **Secure Click and Go Installation**
- **Duct comes preassembled in 5 and 10 foot lengths with duct end fittings**
- **Adjustable Grill for accurate system air balancing**
- **Labor saving installation**

CORE MATERIAL: *Spun nylon polyamid*

THERMAL RESISTANCE: *Available R4.2, R6, R8*

MAXIMUM RELATED VELOCITY: *5500fpm*

MAXIMUM POSITIVE PRESSURE: *6 in. WC*

MAXIMUM NEGATIVE PRESSURE: *5 in. WC*

TEMPERATURE RANGE: *-20°F to +250°F (-29°C to +122°C)*

BEND RADIUS: *1 x diameter*

AVAILABLE SIZES: *3° to 20° (larger sizes on request)*

STANDARD LENGTHS: *25ft*

UL 181 LISTING: *Class 1 Air Duct*

